

### Application:

BC 1500 RM 28V is a compact DC power supply and battery charger with nominal output of 28V 50 Amps. It is designed for the supply of power to sensitive electronics, with or without backup battery.



**NSN 6130-25-152-2277**

The BC 1500 RM 28V input current is power factor corrected and designed for optimum adaptation to weak power sources such as portable generators. The efficiency is very high due to the soft switching converter technology. The BC 1500 RM 28V is intended for mounting in 19" rack systems and occupies 2U (88mm) (3.5") height.

The I/O bus provides several signals: Alarm relay outputs, external battery temperature sensing and a bus for interconnection of multiple BC 1500 RM 28V in a redundant or parallel system. BC 1500 RM 28V is optimal for charging of lead acid batteries. Temperature compensated charging ensures full battery capacity over entire temperature range. The internal temperature sensors control the two redundant fans' speed continuously. The unit is protected from over voltage, short circuit, over current, and over temperature.

### Functions

<b>Under voltage</b>	An alarm is given when the output voltage drops below 20V. The alarm disappears when the voltage rises higher than 21.5V.
<b>Over voltage</b>	An alarm is activated if output voltage exceeds 33.3±1V .
<b>Over temperature</b>	The unit is protected from over temperature.
<b>Output circuit breaker</b>	If an output current higher than aprox. 70 Amps occurs, a circuit breaker is released and rectifier is shut off. Alarm is given.
<b>Input circuit breaker</b>	If an input current higher than 25 Amps occurs, a circuit breaker is released and rectifier is shut off.
<b>Alarms</b>	Alarm signals are fed to a common potential free output, and are indicated in separate LEDs for: <ul style="list-style-type: none"> <li>Power OK</li> <li>Failure</li> <li>Current limit</li> </ul>
<b>Input voltage</b>	When the input voltage decreases to a given level, the rectifier is shut off. When the voltage returns, the rectifier is turned on again.
<b>Connectors</b>	AC: MS3102E16-10P DC: MS3102E22-2S Mon, Par/NTC and Par: Binder 09-0482-00-08
<b>Grounding</b>	Available in front (M5)
<b>Acoustic noise</b>	Max. 55 dBa at 50Hz
<b>Frequency range</b>	45 - 420Hz

# BC 1500 RM EV

## Power supply

### SPECIFICATION

#### Electrical data at 50Hz input voltage

Input voltage	99 – 264 VAC
Power Factor (PF)	> 0.95 (typical 0.99)
Input current at max load	15 Amps @ 115V 400Hz
Input current at max load	8.5 Amps @ 230V 400Hz
Input current @ nom. load	14.6A at 115 VAC @ 400hz
Efficiency at full load	> 85% @ 115 VAC > 87% @ 230 VAC
Nominal output voltage	28 VDC (adjustable 21.5 – 30,0 VDC)
Nominal output current	50 Amps
Load sharing	Better then 10% deviation with 2 - 10 units in parallel
Output voltage ripple and noise	<140mV p-p, 20MHz bandwidth
Output voltage regulation	1,5% zero/max load
Adjustable current limit	5 – 50 Amps
Max input current	17,1A at 99 VAC
Rated input current	14,6A at 115 VAC
Total Harmonic Distortion (THD)	<8% at full load
Short circuit current	≤58.0 Amps

#### EMC

**TREE:** Designed to meet QSTAG 620  
(Transient Radiation Effect on Electronics)

#### Electromagnetic Interference

The power supply meets the requirements of MIL-STD-461D; Ground Army; CE101, CE102, RE102, RS103, CS101, CS114 and CS 116

#### Electromagnetic Pulse (EMP)

Designed to operate without fault after exposure to EMP levels defined in paragraph A5 of QSTAG 244, edition no 3, amendment no. 1, dated 6 June 1983

#### Electrostatic discharge

The power supply meets the requirements of MIL-STD-1686 for ESD

#### Safety

EN 60950

#### Encapsulation

IP32 (front)

#### Cooling

Forced air by 2 speed controlled fans

#### Environmental

#### High temperature

##### Operation

MIL-STD-810E: Method 501.3, Procedure II to 60°C

##### Storage

MIL-STD-810E: Method 501.3, Category A1, hot induced, 71°C

#### Low temperature

##### Operation

MIL-STD-810E: Method 502.3, Procedure II, - 40°C

##### Storage

MIL-STD-810E: Method 502.3, Procedure I, -51°C

#### Temperature shock

MIL-STD-810E: Method 503.3, -51°C - +71°C.  
(Non-operational)

#### Humidity

The power supply operates as specified when exposed to high humidity as per MIL-STD-810E, Method 507.3

#### Vibration

According to MIL-STD-810F, change note 3.  
Table 514.5C-VII. Composite wheeled vehicle vibration exposures figure 514.5C-3

#### Shock

MIL-STD-810E. Method 516.4, Procedure I, functional Shock, 15g 11ms

#### Fungus

Analysis of the degree of inertness to fungus growth of the components in accordance with MIL-HDBK-454

#### Altitude

Designed to meet MIL-STD-810E: Method 500.3, Procedure I (Storage), II (Operational), and III (Rapid decompression), Test altitude is 4750 metres at 57.2Kpa for all tests, except storage. Storage 12195m (40000ft.).

#### Mechanical data

Dimensions	483 x 391 x 88mm (2U)
W x D x H incl. handles	(19 x 15.4 x 3.5")
Weight	11.5kg (25.4lbs)
Cabinet	Standard 19" rack