







Description


Cable connector kits enable the end user to manufacture their own custom input and output cables for ComCompact Series power supplies. Connector kits are available for AC input, AC output, DC input & DC output. Please refer to the table below for ComCompact Series power supply compatibility.




Input Connectors			Output Connectors		
AC Input	AC Input	DC Input (x2)	DC Output	DC Output	AC Output
D 	E 	A 	F 	C 	G 
		B 			
Part Number P600790	Part Number P600791	Part Number P600788	Part Number P600792	Part Number P600789	Part Number P600793
Compatibility ComCompact 2400 ComCompact 2700 ComCompact Dual-Input	Compatibility ComCompact 1200 ComCompact 1500	Compatibility ComCompact 1200 Dual-Input ComCompact 2000 DC/AC	Compatibility ComCompact 2400 ComCompact 2700 ComCompact 1200 Dual-Input	Compatibility ComCompact 1200 ComCompact 1500	Compatibility ComCompact 2000 DC/AC
Connector Allied Electronics Corporation MG06G16-10SA30NS3101E	Connector Allied Electronics Corporation AEC3106G16-10SA30NS3101E	Connectors Allied Electronics Corporation Positive (A) - MGR06G120-2S123A30101ERT Negative (B) - MGR06G120-2S126A30101ERT	Connector Allied Electronics Corporation MG06G22-22PA30101E	Connector Allied Electronics Corporation AEC3106G22-22PA30101E	Connector Allied Electronics Corporation MG06G16-10PA30101E
Description Bayonet connection 3 x crimp sockets	Description Threaded connection 3 x crimp sockets	Description 2 x Bayonet connection 1 x crimp socket per connector	Description Bayonet connection 4 x crimp pins	Description Threaded connection 3 x crimp pins	Description Bayonet connection 3 x crimp pins
Heat Shrink Moulded Boot (not supplied) * TE Connectivity 202K142-25/225-0 (Straight) 222K142-25/225-0 (90 Deg)	Heat Shrink Moulded Boot (not supplied) * TE Connectivity 202K142-25/225-0 (Straight) 222K142-25/225-0 (90 Deg)	Heat Shrink Moulded Boot (not supplied) * TE Connectivity 202K153-25/225-0 (Straight) 222K152-25/225-0 (90 Deg)	Heat Shrink Moulded Boot (not supplied) * TE Connectivity 202K153-25/225-0 (Straight) 222K152-25/225-0 (90 Deg)	Heat Shrink Moulded Boot (not supplied) * TE Connectivity 202K153-25/225-0 (Straight) 222K152-25/225-0 (90 Deg)	Heat Shrink Moulded Boot (not supplied) * TE Connectivity 202K153-25/225-0 (Straight) 222K152-25/225-0 (90 Deg)
General RoHS and Reach compliant. Cadmium free.					
Notes * Heat shrink moulded boot is not supplied as part of the connector kit. The recommended part numbers are suitable for minimum 9mm outside diameter cable.					

Connector Compatibility


Please refer to the table on page 1 for connector compatibility with ComCompact series power supplies.




ComCompact 2400 AC/DC
ComCompact 2700 AC/DC
 (Bayonet Connections)



ComCompact 1200 AC/DC
ComCompact 1500 AC/DC
 (Threaded Connections)



ComCompact 2000 AC/DC (Inverter)
 (Bayonet Connections)



ComCompact 1200 Dual Input 12V
ComCompact 1200 Dual Input 24V
ComCompact 1200 Dual Input 36V
 (Bayonet Connections)